



Portable Power Station

Fanless Cooling / Realtime Power Level Color Display



Universal (Front)



EU (Front)

AC
Charge

Solar
Charge

Vehicle
Charge



Universal (Back)



EU (Back)

UA1101L

Features:



Universal



US / JP



CHN



UK



EU

- 2*AC 230V
- 1*DC12V 10A
- 1*Cigar Lighter 12V / 10A
- 2*Type-C 100W /22.5W
- 2*USB-A QC3.0 18W / 20W
- AC Output Port: Universal / US / JP / CHN / UK / EU
- 1 Year Warranty

- Built-in MPPT Controller & BMS
- High Efficient Fanless Alu Radiator
- LED Lighting
- Realtime Power Level Color Display
- CE / RoHS / UN38.3
- Vehicle Grade Lithium Battery



Parameter:

Model		UA1101L
Built-in Battery (High Quality 18650 Batteries)		1024Wh (LiFe-PO4) (320000mAh/3.2V)
Input Charging	DC Input Charging	(22V/10A) Adapter
	Solar Panel Input	18-24V/10A 200W Max
	Car Input Charging	12-15V/8A Max
AC Output	Output Waveform	Pure Sine Wave
	Output Rated Voltage	100V(95-115V) / 220V(215-225V)
	Output Rated Frequency	50Hz / 60Hz $\pm$ 3Hz
	Rated Output Power	1000W
DC Output	DC Port	1* DC5525 12V / 10A
	Cigarette Lighter Port	1* DC 13V+5%V / 10A (Max 12A+10%)
USB Output	USB-A Port	2* 5V/3A , 9V/2A , 12V/1.5A
	Type-C Port	2* PD 100W / 22.5W
Bulb Type		5W LED (Low, High, SOS, Flash Mode)
Display		LCD Display
Cooling Method		Aluminum Chassis Heat Dissipation And Natural Cooling (Without Fan Design)
Operation Temperature		Charging : 0°C ~ 45°C Discharge: -10° ~ 45°C
Inverter Efficiency (70% load)		> 90%
Multi-protections		Short-circuit Protection Over-current Protection Over-charge Protection Over-discharge Protection SOC Calculation Temperature Protection
Product Size (mm)		192*192*385 mm
Product Weight (kg)		12.7kg
Accessories		1*AC Power Cable 1*AC Power Adapter 1*Car Charging Cable 1*User Manual

Packaging Information:

UA1101L
-N.W/pc: 13kg
-G.W/carton: 16kg
-Carton Size: 315*285*320mm
-20GP: 460pcs
-40HQ: 1000pcs